

IN THE CLAIMS:

Please amend claims 1, 17 and 28 as follows:

1. (Amended herein) A method of manufacture, said method comprising:
forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication;
spacing the at least one electromagnetic shield apart from the at least one antenna by using a spacer that is oriented to provide a separation between the at least one electromagnetic shield and the at least one antenna, wherein the electromagnetic shield has a top panel and a plurality of side panels.
2. (canceled)
3. (original) The method of Claim 1, wherein the at least one antenna comprises: a Planar Inverted F Antenna (PIFA).
4. (original) The method of Claim 1, wherein the at least one antenna comprises: a slot antenna.
5. (original) The method of Claim 1, wherein the at least one antenna comprises: a dipole antenna.
6. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:
forming the at least one electromagnetic shield or the at least one antenna from a metal.
7. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:

forming the at least one electromagnetic shield or the at least one antenna from a conductive material.

8. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:

punching the at least one electromagnetic shield or the at least one antenna from a sheet of conductive material.

9. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:

stamping the at least one electromagnetic shield or the at least one antenna from a sheet of conductive material.

10. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:

bending a piece of conductive material.

11. (original) The method of Claim 1, wherein said forming at least one electromagnetic shield and at least one antenna in substantial electrical current communication comprises:

molding the at least one electromagnetic shield and the at least one antenna.

12. (original) The method of Claim 11, wherein said molding the at least one electromagnetic shield and the at least one antenna comprises:

injection molding the at least one electromagnetic shield and the at least one antenna.

13. (original) The method of Claim 1, further comprising:

placing the at least one electromagnetic shield and the at least one antenna in proximity to an electromagnetic source or sink.

14. (previously presented) The method of Claim13, wherein said placing the at least one electromagnetic shield and the at least one antenna in proximity to an electromagnetic source or sink further comprises:

placing an antenna feed of the at least one antenna in electrical current communication with an antenna feed connection of a printed current board.

15. (original) The method of Claim13, wherein said placing the at least one electromagnetic shield and the at least one antenna in proximity to an electromagnetic source or sink further comprises:

placing the at least one electromagnetic shield and the at least one antenna in proximity to electrical circuitry selected from an electrical-circuitry group including but not limited to electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program, electrical circuitry forming a memory device, electrical circuitry forming a transmitter, electrical circuitry forming a receiver, and electrical circuitry forming a communications device.

16. (original) The method of Claim15, wherein the electrical circuitry comprises:
a printed circuit board having the electrical circuitry.

17. (Amended herein)A system comprising:
at least one electromagnetic shield and at least one antenna formed in substantial electrical current communication;

a spacer between the at least one electromagnetic shield and the at least one antenna, the spacer oriented to provide a separation between the at least one electromagnetic shield and the at least one antenna, wherein the electromagnetic shield has a top panel and a plurality of side panels.

18. (canceled)
19. (original) The system of Claim 17, wherein the at least one antenna comprises:
a Planar Inverted F Antenna (PIFA).
20. (original) The system of Claim 17, wherein the at least one antenna comprises:
a slot antenna.
21. (original) The system of Claim 17, wherein the at least one antenna comprises:
a dipole antenna.
22. (original) The system of Claim 17, wherein said at least one electromagnetic
shield and at least one antenna formed in substantial electrical current communication comprises:
said at least one electromagnetic shield or at least one antenna formed from a metal.
23. (original) The system of Claim 17, wherein said at least one electromagnetic
shield and at least one antenna formed in substantial electrical current communication comprises:
said at least one electromagnetic shield or at least one antenna formed from a conductive
material.
24. (original) The system of Claim 17, further comprising:
the at least one electromagnetic shield and the at least one antenna in proximity to an
electromagnetic source.
25. (original) The system of Claim 24, wherein the at least one electromagnetic
shield and the at least one antenna in proximity to an electromagnetic source comprises:
an antenna feed of the at least one antenna in electrical communication with an antenna
feed connection of a printed circuit board.
26. (original) The system of Claim 24, wherein the at least one electromagnetic

shield and the at least one antenna in proximity to an electromagnetic source comprises:

the at least one electromagnetic shield and the at least one antenna in proximity to electrical circuitry selected from an electrical-circuitry group including but not limited to electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program, electrical circuitry forming a memory device, electrical circuitry forming a transmitter, electrical circuitry forming a receiver, and electrical circuitry forming a communications device.

27. (original) The system of Claim 26, wherein the electrical circuitry comprises: a printed circuit board having the electrical circuitry.

28. (Amended herein) A wireless device comprising:
at least one electromagnetic shield and at least one antenna formed in substantial electrical current communication;

a spacer between the at least one electromagnetic shield and the at least one antenna, the spacer oriented to provide a separation between the at least one electromagnetic shield and the at least one antenna, wherein the electromagnetic shield has a top panel and a plurality of side panels.

29. (canceled)

30. (original) The wireless device of Claim 28, further comprising:
said wireless device selected from the wireless-device group including but not limited to at least one cellular-enabled wireless device, at least one TDMA-enabled wireless device, at least one CDMA-enabled wireless device, at least one GPS-enabled wireless device, and at least one email-enabled wireless device.